HOGAN PRODUCTS & SERVICES

INSIGHT LED CITADEL SEALED FIXTURE



DETAILS

IMPLE MOUNTING SYSTEM

- 6' or 10' POWER CORD WITH or WITHOUT 3-PRONG PLUG
 DURABLE + MAINTENANCE FREE
- SIZES: WL2 2' [Nominal Length] x 7.33" [W] x 27.68" [L] x 4.13" [D]
 WL4 4' [Nominal Length] x 7.33" [W] x 51.81" [L] x 4.13" [D]
 WL4*— 4' [Nominal Length] x 14.61" [W] x 51.91" [L] x 5.95" [D]





CITADEL PREMIUM SEALED LED FIXTURE FEATURES

- APPROX. 120 125 LUMENS PER WATT
- PROTECTION FOLDBACK CIRCUIT FOR AMBIENT TEMPS OVER 140°F
- HEAVY DUTY FIBERGLASS ENCLOSURE FOR LONG FIXTURE LIFE
- LINEAL RIBBED LENS
- NO MAINTENANCE NO LAMPS OR BALLASTS TO REPLACE!
- 5-YEAR COMPONENT WARRANTY
- AMBIENT TEMP -40°F TO 140°F
- UNIVERSAL DIMMABLE DRIVER 120 277 VAC
- COLOR TEMPERATURE: 4000K OR 5000K
- SIMPLE BRACKET MOUNTING SYSTEM
- DIRECT MOUNT TO CEILING OR BEAM
- PENDANT MOUNT
- CHAIN HANG OR CABLE MOUNT WITH OR WITHOUT OPTIONAL BAIL
- CSA & UL 1598 CERTIFIED [SELECT MODELS ARE DLC LISTED]
- BUY AMERICA ACT COMPLIANT

CITADEL SPECIFICATIONS

Model	Nominal Wattage	Lumens @4000K	Lumens @5000K	Lumens per watt
WL2-3200	25	3100	3170	125
WL4-4000	32	3900	4000	125
WL4-6000	50	6200	6340	125
WL4-12000	100	12400	12680	125
WL4*-18000	150	18600	19020	135
WL4*-24000	200	24800	25360	125



FOR MORE INFORMATION: sales@hoganproductsllc.com





www.HOGANPRODUCTSLLC.com

MADE IN USA